



The robust and reliable, **TM 22** hand pallet trucks are ideal for daily, safe and easy transport of any type of goods, in any situation, over shorter distances in **ATEX** classified areas.

We produce a wide range with different options, including capacities up to 3 tons, carbon steel chassis with **AISI 304** stainless steel clad forks or complete stainless-steel chassis, customised lengths and widths across forks, and models with scissor lift.

All our **ATEX** pallet trucks are suitable for use in areas classified with the presence of **Group IIA/IIB** gases and **IIIC** conductive dust. On request, we can supply models suitable for areas classified with **Group IIC** gases (hydrogen and acetylene) and also special versions suitable for handling drums or products with special dimensions.

Easy to manoeuvre thanks to ergonomic controls.

Permanently lubricated connections and maintenance-free hydraulic pumps with special lowering valve ensure that the hand pallet truck is always efficient and ready for use.

Group:	II
Category:	2GD
Gas group:	IIB
Dust group:	IIIC
Temperature class:	T6
Max surface temperature:	T85°C
Reference to Standards and Directives:	2014/34/EU "ATEX" e EN 1755:2015

■ TECHNICAL FEATURES

CHARACTERISTICS	1.1	Manufacturer		EXCEN
	1.2	Designation type		TM22
	1.3	Load Capacity	Q kg	2.200
	1.4	Load centre distance	c mm	600
	1.5	Wheelbase	Y mm	1.110
WT.	2.1	Tare weight	kg	69
WHEELS	3.1	Tyres		Steering wheels: (A) Antistatic rubber Roller: single nylon (GN), tandem nylon (BN), single polyurethane (GV), tandem polyurethane (BV)
	3.2	Tyre size and number, front		2x Ø 170x50
	3.3	Tyre size and number, rear		2/4x Ø 82x96
	3.4	Tread width, front	b10 mm	109
	3.5	Tread width, rear	b11 mm	370
BASIC DIMENSIONS	4.4	Lift (h3)	h3 mm	122
	4.14	Stand height, elevated	h12 mm	207
	4.15	Height, lowered	h13 mm	85
	4.19	Total length	l1 mm	1.525
	4.20	Length including fork shank	l2 mm	373
	4.21	Total width	b1 mm	524
	4.22	Fork dimensions	s/e/l mm	55 x 154 x 1152
	4.25	Width across forks	b5 mm	524
	4.32	Ground clearance centre of wheelbase	m2 mm	30
4.33	Aisle width (pallet 800x1200 length)	Ast mm	1.784	

■ DIMENSIONS

